

Non Ferrous Strap



Contact

info@titan-asiapacific.com
+61 8 8240 9000
2A Capelli Road, Wingfield, South
Australia, 5013



Packing Steel Strap

Stainless steel for the precious products

In addition to all the heavy, robust and resistant products that are strapped and transported every day, there are of course other packages that demand exceptional care and attention due to their high quality.

Exclusive exterior façades for buildings are just one example. In such cases, the proven V2A strap designed for the highest demands is used.

In contrast to the usual manufacturing process of TITAN steel straps, no thermal processing takes place here.

This not only leads to extreme elongation properties, but also guarantees absolute residue-free strapping of luxury products. Corrosion? Not a trace!

Technical Data

Dimensions	from 16 x 0.5 mm bis 19 x 0.5 mm from 1/2 x 0.020" to 0.8 x 0.020"
Tensile strength	≥ 1,050 - 1,250 N/mm ²
Breaking load approx.	up to 14,800 N 3,310 lbf
Elongation (A5) min approx.	≥ 15-25 %
Surface	blank: surface like cold rolled strip with rolling emulsions or additional oil/ wax zinc plated: on request, waxed

Coiling	ribbon wound, oscillated wound
Form of delivery	skid pallets, frames for jumbo coils, special skids on request
Certification	quality management: DIN EN ISO 9001 energy management: DIN EN ISO 50001