



Reduced to the essentials – inexpensive and good

In some application areas, the most cost-effective solution is needed.

For example, if no high demands are placed on the system breaking load. Using savings potentials is the motto when using blank strap. However, you do not have to do without the typical TITAN quality when using blank strap:

Blank strap has a waxed surface that prevents cold welding during processing with hand-held tools and stands thanks to the established rounding as well as its sibling products for minimal risk of injury.

TITAN blank strap is the efficient and at the same time safe choice for short use, for example in wood processing and for building materials



Contact Details

Unit 1, 73-75 Cormack Road Wingfield SA 5013

+61 8 8240 9000

admin@titan-asiapacific.com

Packing Steel Strap

Technical Data	
Dimensions	from 12 x 0.38 mm to 32 x 1.00 mm from 1/2 x 0.015" to 1 1/4 x 0.040"
Tensile strength	≥ 600 N/mm ²
Breaking load approx.	up to 19,000 N 4,300 lbf
Elongation (A5) min approx.	≥ 3%
Surface	blank: surface like cold rolled strip with rolling emulsions or additional oil/ waxn zinc plated: on request, waxed
Coiling	ribbon wound
Form of delivery	skid pallets, frames for jumbo coils, special skids on request
Certification	quality management: DIN EN ISO 9001 energy management: DIN EN ISO 50001