



## Exciting manual tensioning

It would be wrong to neglect the market for mobile and flexible use of tensioning devices for steel strapping.

The purely manual operation eliminates the need for compressed air and makes the HR32 portable.

The low weight of 3.9 kg contributes to mobility. Simple maintenance and the robust, ergonomic design take the same line.

The HR32 is suitable for circular and flat packages strapped with strap widths of 19, 25 or 32 mm.

It is designed for the use of seals that the sealer HV from TITAN joins. This is teamwork!

### Contact Details

Unit 1, 73-75 Cormack Road Wingfield SA 5013

+61 8 8240 9000

admin@titan-asiapacific.com



**Tensioner for steel strap**

## Technical Data

Kind of drive (sealing)	Manually
Dimensions	450 x 110 x 200 mm (L x W x H) 17.7 x 4.3 x 7.9" (L x W x H)
Weight	3.9 kg 8.6 lb

## Strap/Joint

Type of strap	Steel strap
Strap	Automatenband MEGABAND®
Strap width	19, 25, 32 mm 3/4" ; 1" ; 1 1/4"
Strap thickness	0.80 - 1.00 mm (for Automatenband) 0.80 mm (for MEGABAND®) 0.031 - 0.039" (for Automatenband) 0.031" (for MEGABAND®)

## Application

Strapping of round and flat packages (e.g. sectional steel, bundles, pipes, coils, etc.) for mobile use.