




Convenience through air pressure

With the PKE-HD, TITAN has developed a hand-held tool for standard and high-performance straps up to 19 x 0.8 mm that is unrivalled on the market.

As the big brother of the PKE and cousin of the HKE-HD, it combines the key features of the E-Series with a comfortable, fully pneumatic function and specialisation in straps of 19 mm width.

This makes it easy to use the tool in tough applications such as sheet metal packages. The sealless joint with three notches established by TITAN holds together what belongs together.

The high and uniform strap tension ensures the highest reliability.



Pneumatic strapping tool for steel strap

Contact Details

Unit 1, 73-75 Cormack Road Wingfield SA 5013

+61 8 8240 9000

admin@titan-asiapacific.com

Technical Data	
Kind of drive (tensioning)	Pneumatic
Tension force	up to 7,000 N
Kind of drive (sealing)	Pneumatic
Strap feeding speed	0.15 m/s 0.5 ft/s
Dimensions	390 x 150 x 270 mm (L x W x H) 390 x 163 x 270 mm (L x W x H) (PKE-HD) 15.4 x 5.9 x 10.6" (L x W x H) 15.4 x 6.4 x 10.6" (L x W x H) (PKE-HD)
Weight	11.5 kg 11.4 kg (PKE-HD) 25.3 lb 25.1 lb (PKE-HD)
Air pressure	min. 5 bar flow pressure (for 19 x 0,63 mm MEGABAND®) max. 6 bar flow pressure min. 5 bar flow pressure (for 3/4" x 0.025" MEGABAND®) max. 6 bar flow pressure
Air consumption (during tensioning)	0.6 m ³ / min. 21.18 ft ³ / min.
Cross-section	information currently not available
Handarm vibration	< 2.5 m/s ²
Noise level	78 dB (A)

Strap/Joint	
Type of strap	Steel strap
Strap	Automatenband MEGABAND® Megaflex
Strap width	13, 16, 19 mm 1/2", 5/8", 3/4"
Strap thickness	0.50 - 0.80 mm (for Automatenband, Megaflex) 0.50 - 0.63 mm (for MEGABAND®) 0.02 - 0.031" (for Automatenband, Megaflex) 0.02 - 0.025" (for MEGABAND®)
Kind of seal	Sealless-joint
Sealing strength (depending on strap quality, strap dimensions)	approx. 75% of the strap breaking load

Minimum bearing Area

Flat package

150 mm 5.9"

Application

Strapping of flat packages (e.g. palletized goods) for stationary use.