



## The ultimate battery powerhouse

The TA 750 is the absolute top-of-the-range model in the TA family - with performance values that are second to none in the battery-powered hand-held segment: Thanks to the proven rechargeable battery of 36 Volt, it delivers a tensioning force of up to 7,000 N.

Strap widths in the range between 19 and 32 mm are thus routine. This kind of power development obviously requires maximum control. No problem for the TA 750! Other advantages reserved for users of TITAN hand-held tools are the excellent handling properties of the TA series, the extremely simple and intuitive operation using two buttons and, finally, the low weight.

Strapping in the steel and sheet metal sectors as well as of coils can be done with the TA 750 in no time at all.

The power is in your fingertips.



## Battery powered strapping tool for plastic strap

### Contact Details

Unit 1, 73-75 Cormack Road Wingfield SA 5013

+61 8 8240 9000

[admin@titan-asiapacific.com](mailto:admin@titan-asiapacific.com)

Technical Data	
Kind of drive (tensioning)	Electric
Tension force	2,700 - 8,000 N (adjustable)
Kind of drive (sealing)	Electric
Power supply system	36 V / 2.0 Ah / 72 Wh
Strap feeding speed	12 m/min. 39.4 ft/min.
Dimensions	300 x 150 x 200 mm (L x W x H) 11.8 x 5.9 x 7.9" (L x W x H)
Weight	6.4 kg 14.1 lb
Handarm vibration	2.2 m/s <sup>2</sup>
Noise level	81 dB (A)

Strap/Joint	
Type of strap	Plastic strap
Strap	PP PET
Strap width	19 mm 3/4" 25, 32 mm 1" ; 1 1/4"
Strap thickness	0,80 - 1,40 mm 0.031 - 0.055" 1,00 - 1,30 mm 0.039 - 0.051"
Kind of seal	Friction-weld joint
Sealing strength (depending on strap quality, strap dimensions)	approx. 75% of the strap breaking load

Application
Strapping of flat packages (e.g. palletized goods) for mobile use.